

Ex-Monitor



Quotation (Ex-works)

Item	Model No	Specification
1	1900	19-inch industrial grade monitor, 304 stainless steel, 2 outlet ports, HDMI port
2	2200	21.5 inch industrial grademonitor, 304 stainless steel, 2 outlet ports, HDMI port

Specification

Ex parameter	
Explosion-proof marks	Ex d IIB T6 Gb
Protection level	IP54
Using range	It can be used in zone 1 and zone 2 sites of II A, Nb, T1 ~ T6 groups of explosive mixture of combustible gas, steam and air, and explosive dangerous sites of zone 21 and zone 22 where combustible dust mixes with air
Electrical parameters	
Working voltage	AC85~265V /DC12V/ Power supply for optional system
Working current	≤3A
The screen size	19 "/21.5" industrial LCD panel and LCD driver board
Signal input interface	RJ45/BNC/HDMI/VGA
Screen resolution	1024*768/1280*1024/1920*1080
The screen brightness	300-500cd/M ²
Backlight model	CCFL/OLED
According to the color	16.2M
Corresponding time	8ms
contrast	500:1
Image	
Input interface	HDMI
Output interface	HDMI
Resolution	Supports 1080p resolution
Frequency	60hz
Control mode	Panel keys, remote control
Image segmentation	1/2 /4
Mechanical parameters	
The material	304 stainless steel
The weight of the	25kg
installation	Built-in/hoisting/seat mounting
Cable lead-in device	G3/4*7
Environmental indicators	
Atmospheric pressure	80~106KPa
Environment temp	-20°C~+60°C
Relative humidity	≤95%RH(+25°C)