

RPZ85848-HNF-PA-FL

8MP 48x Starlight Laser AI Network Positioning Camera



- 1/1.8" 8Megapixel STARVIS™ CMOS
- 48x optical zoom
- Starlight technology
- Max. 25/30 fps@8M
- Laser distance up to 1000m
- H.265 encoding
- Two-way audio
- IP67
- Auto-tracking
- Perimeter protection
- Face Recognition

System Overview

AI series products adopt the most advanced AI technologies, including deep learning algorithms that primarily target people and vehicles, which provide higher flexibility and accuracy for end-users. This enables the AI series to offer various advanced applications such as Face Recognition, ANPR, Metadata, People Counting, and traffic data statistics. The complete lineup of AI includes network (PTZ) cameras, network video recorders, servers, and more devices. Beyond seeing the world, the power of AI allows devices to perceive the environment and understand the world in a better way.

Functions

Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, and more, and uses secondary recognition during target detection to improve alarm accuracy.

Starlight Technology

For challenging low-light conditions, Starlight Ultra-low Light Technology offers the best in light sensitivity, capturing color in vivid detail, even in lighting as low as 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, producing clear images in dark environments.

PFA Technology

PFA technology has introduced new methods of judgment that ensure the accuracy and predictability of the direction of subject distance adjustment. The result is a set of advanced focusing algorithms that ensure image clarity when zooming and that shorten focus time. This makes the camera highly advanced in its functions, substantially improving the quality of your experience.

Environment (–40 °C to +70 °C, IP67)

Developed to operate in extreme conditions, this camera can function in temperatures ranging from –40 °C to +70 °C (–40 °F to +158 °F) at 95% humidity. It was subjected to rigorous dust and water immersion tests, gaining its IP67 Ingress Protection certification, making it suitable for demanding outdoor applications.

Auto-tracking

This feature controls the pan, tilt and zoom actions of the camera to automatically track an object in motion, to keep it in view of the camera. Tracking can be triggered manually or automatically by defined rules. Once a rule is triggered, the camera can zoom in and track the defined target automatically.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, a flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality videos without straining the network. Smart H.265+ technology outranks standard H.265 video compression, reducing bit rate and storage requirements by up to 70%.

Scenes

The PTZ AI network camera adopts advanced CNN deep learning algorithms to support Perimeter Protection. This highly accurate camera possesses a wide monitoring range and the PFA algorithm, allowing it to always present a clear, focused image while zooming. Leveraging the latest in starlight technology, the camera has strong low light performance, smooth controls, high-grade protection, and produces high quality images, meeting most of the requirements of video surveillance applications.

RPZ85848-HNF-PA-FL

8MP 48x Starlight Laser AI Network Positioning Camera

Technical Specification

Camera

Image Sensor	1/1.8" CMOS
Pixel	8MP
Max. Resolution	3840(H) x 2160(V)
ROM	8GB
RAM	2GB
Electronic Shutter Speed	1/1s-1/30,000s
Scanning System	Progressive
Minimum Illumination	Color: 0.005Lux@F1.4 B/W: 0.0005@F1.4 0Lux (Laser on)
Illumination Distance	1000m (3280.84ft))
Illumination On/Off Control	Zoom Prio / Manual / Off
Illumination LEDSS	1 (Laser)
Wiper	Yes

Lens

Focal Length	6.25mm - 300mm			
Max. Aperture	F1.4 - F4.5			
Field of View	H: 64.87°–1.77°; V: 38.07°–1.01°; D: 72.18°–2.04°			
Optical Zoom	48x			
Focus Control	Auto / Semi-Auto / Manual			
Close Focus Distance	0.5m - 2m (1.64ft – 6.56ft)			
Iris Control	NA			
DORI Distance	Detect	Observe	Recognize	Identify
	6,000m (19,685.04ft)	2,381m (7,811.68ft)	1,200m (3,937.01ft)	600m (1,968.50ft)

PTZ

Pan/Tilt Range	Pan: 0° to 360° endless Tilt: -45° to 90°
Manual Control Speed	Pan: 0.1°/s - 160°/s Tilt: 0.1°/s - 60°/s
Preset Speed	Pan: 160°/s Tilt: 60°/s
Presets	300
Tour	8 tours (up to 32 presets per tour)
Pattern	5
Scan	5
Power-off Memory	Yes
Idle Motion	Preset / Tour / Pattern / Scanning
PTZ Protocol	Pelco-P/D (Auto recognition)

Intelligence

Video Metadata	Support human body, human face, motor vehicle and non-motor vehicle image capture and attribute extraction.
IVS (Perimeter Protection)	Tripwire; intrusion; climbing fences; loitering detection; abandoned/missing object; fast moving; parking detection; people gathering; vehicle/human alarm classification.
Face Recognition	Yes

Video

Compression	H.265; H.264M; H.264H; MJPEG; Smart H.265; Smart H.264
Streaming Capability	3 Streams
Resolution	8M (3840 × 2160); 4M (2560 × 1440); 1080p (1920 × 1080); 960p (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Video Frame Rate	Main stream: 8M/4M/1080p/960p/720p (1-25/30 fps) Sub stream 1: D1/VGA/CIF (1-25/30 fps) Sub stream 2: 1080p/960p/720p (1-25/30 fps)
Bit Rate Control	CBR; VBR
Bit Rate	H.264: 3328-16384 kbps H.265: 1280-9984 kbps
Day/Night	Auto (ICR); Color; B/W
BLC	Yes
WDR	Yes
HLC	Yes
White Balance	Auto / Indoor / Outdoor / Tracking / Manual / Sodium lamp / Natural light / Street lamp
Gain Control	Auto / Manual
Noise Reduction	2D NR / 3D NR
Motion Detection	Yes
Region of Interest (ROI)	Yes
Defog	Optical
Digital Zoom	16x
Image Rotation	180°
Privacy Masking	Up to 24 areas can be set, with up to 8 areas in the same view
S/N Ratio	≥55 dB

Audio

Audio Compression	G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1; G729; PCM
-------------------	---

RPZ85848-HNF-PA-FL

8MP 48x Starlight Laser AI Network Positioning Camera

Network

Network Port	RJ-45 (10/100Base-T)
Network Protocol	HTTP; HTTPS; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; IPv6; 802.1x; QoS; FTP; UPnP; ICMP; SNMP; IGMP; RTP; PPPoE; RTMP; TCP
Interoperability	ONVIF (Profile S&G&T); GB/T28181; CGI
Streaming Method	Unicast/Multicast
User/Host	20 (Total bandwidth 64M)
Storage	FTP; Micro SD card (512GB); NAS
Browser	IE7 and later versions Chrome 45 and later versions Firefox 52ESR and earlier versions Safari
Mobile Client	iOS/Android

Port

Analog Output	1 channel (CVBS output, BNC)
RS-485	1 (baud rate: 1200bps~115200bps)
Audio Input	1 channel (LINE IN, bare wire)
Audio Output	1 channel (LINE OUT, bare wire)
Two-way Audio	Yes
Alarm Input	7 (on-off value input: 0~5 VDC)
Alarm Output	2
Alarm Linkage	Capture; preset; tour; pattern; recordings on SD card; alarm digital input; client E-map; send email
Alarm Event	Motion/tampering detection; audio detection; network disconnection detection; IP conflict detection; decoder state detection; memory card state detection; memory space detection; power exception detection

Power

Power Supply	36VDC / 5A (±25%)
Power Consumption	Basic: 22W Max: 63W (illuminator + wiper + PTZ)



Environment




Operating Temperature	-40°C ~ 70°C (-40°F ~ +158°F)
Operating Humidity	≤95%
Protection	IP67; TVS 6000V lightning proof; surge protection; voltage transient protection

Structure

Casing	ADC12
Product Dimensions	344.6mm × 252.2mm × 499.8mm (13.57" × 9.93" × 19.68") (L × W × H)
Net Weight	15.4Kg (33.95lb)
Gross Weight	23.7Kg (52.25lb)

Accessories

Included	Optional
 DC36V/5A Power Adapter	 RPF8741W Wall Mount Bracket

Plane Mount	Plane Mount	Wall Mount
		

Dimensions (mm[inch])

