

# RPZ8641WDL-Z37

4MP 37x Starlight Laser PTZ Network Camera



- 1/1.8" STARVIS™ CMOS
- 37x optical zoom and 16x digital zoom
- Support face, human and vehicle detection and capture
- Support smoke and fire detection as well as smart motion detection
- Auto tracking and perimeter protection based on deep learning
- Intelligent analysis: intrusion, single line crossing, double line crossing, loitering, wrong-way, illegal parking and people counting
- True WDR, 3D DNR, ICR, HLC, BLX, Defog and EIS
- Laser illumination distance up to 600m
- IP66

# RPZ8641WDL-Z37

## 4MP 37x Starlight Laser PTZ Network Camera

### Technical Specification

#### Camera

Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	2592(H)×1520(V)
Min. Illumination	Color: 0.001Lux@(F1.5, AGC ON), B/W: 0.0001Lux@(F1.5, AGC ON), 0Lux with IR
Electronic Shutter	Auto/Manual, 1/5 to 1/20,000s
Day & Night	Auto (ICR)
Wiper	Support

#### Lens

Focal Length	6.8mm to 251mm, 37x optical zoom
Max. Aperture	F1.5 to F4.8
Angle of View	H: 60.7°~2.33° V: 36.8°~1.38°
Zoom Speed	Approx. 2.5s
Iris Control	Auto/Manual
Focus Control	Auto/Manual/Semi-automatic
Digital Zoom	16x

#### DORI Distance

Lens	Detect	Observe	Recognize	Identify
Tele	100m (328.1ft)	40m (131.2ft)	20m (65.6ft)	10m (32.8ft)
Wide	4,000m (13,123.4ft)	1,600m (5,249.3ft)	800m (2,624.6ft)	400m (1,312.3ft)

#### Illuminator

Illuminator Type	IR + Laser
Illumination Distance	Up to 600m (1,968.5ft)
Smart Illumination	Support

#### PTZ

Pan/Tilt Range	Pan: 0° to 360° endless Tilt: -10° to +90°
Pan Speed	Pan speed: 0.1° to 300°/s Preset speed: 300°/s
Tilt Speed	Tilt speed: 0.1° to 300°/s Preset speed: 300°/s
Presets	400
Patrol Scan	6 Track, 12 Scan, 12 Patrol (up to 32 presets each patrol)
Power-Off Memory	Support
3D Positioning	Support
PTZ Status Display	Support
Idle Motion	The time can be set (1-240 minutes), and functions such as preset positions, patrols, scans, and tracks can be run

#### Video

Streaming Capability	3 Streams
Stream/Frame Rate	Stream1: 2592×1520, 2304×1296, 1920×1080, 1280×720 @25/30fps Stream2: D1, VGA, CIF @25/30fps Stream3: VGA, CIF, QVGA @25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 200kbps to 12Mbps Stream2: 100kbps to 6Mbps Stream3: 100kbps to 3Mbps
Smart Encoder	Support
Region of Interest (ROI)	Support

#### Audio

Audio Compression	G.711, RAW_PCM
Audio Bit Rate	64Kbps (G.711), 128Kbps (RAW_PCM)

# RPZ8641WDL-Z37

## 4MP 37x Starlight Laser PTZ Network Camera

### Image

Image Adjustment	Brightness, Sharpness, Contrast, Saturation
Mirror	Support
Exposure Mode	Auto/Manual
White Balance	Auto/Manual
Day/Night Setting	Auto, Day, Night, Time
Noise Reduction	2D/3D DNR
Image Enhancement	HLC, BLC, Defog, EIS
Wide Dynamic Range	True WDR
S/N Ratio	50dB
Privacy Masking	Support 40 zones, mask color configurable

### Smart Function

Basic Event	Motion detection alarm, Disk alarm, Network alarm
Multi-Object Detection	Support face, human, vehicle detection and capture
Intelligent Analysis	Intrusion, Single line crossing, Double line crossing, Loitering, Wrong-way, Illegal parking, Smart motion Detection (support the accurate detection of vehicle and human)
Smoke & Fire Detection	Support
People Counting	Support
Smart Tracking	Support

### Network

Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, RTSP/RTP/RTCP, IGMP/Multicast, SMTP, DHCP, NTP, DNS, DDNS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, TLS
Interoperability	ONVIF, SDK, CGI
Streaming Method	Multicast
Max. User Access	10 Users
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge
Language	English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian. Default: English

### Interface

Network Interface	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio Interface	1ch Input, 1ch Output
Alarm Interface	1ch Input, 1ch Output
RS-485	Support
CVBS Interface	Support
SD Card Slot	Built-in, up to 1TB

### Electrical

Power Supply	24VAC/36VDC/PoE++ (IEEE 802.3bt), Standard Equipped: 36VDC
Power Consumption	Less than 45W
Operating Temperature	-40°C to 60°C (-40°F to 140°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP66, TVS4000V
Certifications	CE; FCC; NDAA Sec. 889
Casing	Metal
Dimensions	Φ226mm x 362.8mm (Φ8.9" x 14.28")
Net Weight	5.5Kg (12.13lb)

# RPZ8641WDL-Z37

4MP 37x Starlight Laser PTZ Network Camera

## Accessories

Optional:



RBK349  
Wall Bracket



RBK348A  
Ceiling Bracket



RBK605  
Corner Mount



RBK604B  
Pole Mount



RBK367  
Junction Box



RBK355  
Wall Bracket



RBK358  
Corner Mount



RBK359  
Pole Mount

## Dimensions (mm)

